



LUBRICATE ALL SEALS WITH CLEAN
HYDRAULIC OIL PRIOR TO ASSEMBLY.
DO NOT USE SILICONE BASED LUBRICANTS.



| N/A | N/A | 46100016 | SPRING KIT | | | NOTED |
|-----|-----|----------|---------------------------------|---------------|--------------|------------|
| N/A | N/A | 6V200105 | SEAL KIT, FKM | | | NOTED |
| N/A | N/A | 46000025 | SEAL KIT, STANDARD | | NOTED | |
| 6 | 1 | 39V53001 | WIPER, PRESS-IN, (1/4) | X | X | |
| 5 | 1 | 82030502 | GLAND, THRD CYL, 980 LB | | | |
| 4 | 1 | 48010503 | PISTON, CYL, TB, 4.4KN, 32 STRK | | | |
| 3 | 1 | 39010012 | SEAL, BEVEL, 5/16 X 3/32 X 1/2 | X | 39V10012 | |
| 2 | 1 | 23312009 | SPRING, COMPRESSION | | | X |
| 1 | 1 | 23002004 | RETAINING RING, SPIRAL, INTL | X | X | X |
| No. | QTY | PART No. | DESCRIPTION | Std. Seal Kit | FKM Seal Kit | Spring Kit |

PARTS LIST



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED

PARTS LIST, ASSY, CYL, TB, 4.4KN, 32 STRK, SA

42001011

42001011F

SIZE
A

MPL2078

REV
K

SHEET 1 OF 1

| | | | | |
|---------|------------------------|--|------------|----------|
| K | 4030 | RELEASE | JDW | 02/17/20 |
| REV | IN ACCORDANCE WITH ECN | EFFECTIVE DATE | REVISED BY | DATE |
| DRW BY: | BUSH | DRAWING STATUS: Released | | |
| DATE: | 06/28/95 | PRODUCTION APPROVED FOR RELEASED STATUS ONLY | | |

FORM FEG035_PL_ASIZE, REV. B