



Cavity Dimensions (mm)							
Model No.	G	B	C	D	E	Copper Gasket Torque (Nm)	Composite Gasket Torque (Nm)
42-1010-00*	M16x1,5	14,52±0,15	13,84±0.13	8	4	40	20
42-1010-01*	M20x1,5	18,52±0,15	16,81±0.13	9,5	4	54	30
42-1010-02*	M28x1,5	26,52±0,15	23,44±0.13	16	7	68	35
42-1010-03*							
42-1010-04	M35x1,5	33,52±0,15	31,19±0.13	22	7	N/A	50

*Cylinders may need to be re-torqued after a break-in period of 3 weeks or 2,500 cycles for both gasket styles.

INSTALLATION INSTRUCTIONS



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED

Cavity Dimensions

Cartridge Mounted Cylinders

-SEE CHART-

SIZE
A

1SMV2100

REV
B

SHEET 1 OF 1

B	3041	RELEASE	BCD	11/9/16
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY: JDW	DRAWING STATUS: Released			
DATE: 8-8-11	PRODUCTION APPROVED FOR RELEASED STATUS ONLY			

FORM FEG041-IS.ASIZE, REV. B