



6 USE VEKTEK AT200166 TO INSTALL

5 INSTALL WITH LIPS FACING BORE USE VEKTEK AT200193 TO INSTALL

BODY NON-REPLACEMENT PART



3 2

8 1

4 INSTALL WITH LIPS FACING PLUNGER THREADS

4 1

1 1

2 2

7 1

APPLY MEDIUM STRENGTH THREADLOCKER AND TORQUE TO 180FT-LB USE VEKTEK AT200180 TO INSTALL

LUBRICATE ALL SEALS WITH CLEAN HYDRAULIC OIL PRIOR TO ASSEMBLY DO NOT USE SILICONE BASED LUBRICANTS

NO	QTY	PART NO	DESCRIPTION	STD SEAL KIT
1	1	23355016	SPRING, COMPRESSION	
2	2	23520005	PIN, SPRING, SLOTTED, 1/4 X 7/8, SST	
3	2	30601144	PLUG, SOCH, SAE 4	
4	1	39052051	SEAL, U-CUP, 2 X 3/16 X 2 3/8	X
5	1	39052055	SEAL, LL, (1-1/16 X 1/8 X 1/8 X 1-5/16)	X
6	1	39053052	WIPER, PRESS-IN, (1-1/16)	X
7	1	82040015	CAP, CYL, BB, PULL, 17100LB	
8	1	82140017	PLUNGER, CYL, CM, PULL, 17100LB	
N/A	N/A	60201122	KIT, SEAL, CYL, BB, PULL, 17100LB	NOTED

PARTS LIST



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED
20-1121-00

PARTS LIST, ASSY, CYL, BB, PULL, 17100LB

5/8-11 PLNGER THD

SIZE
A PL2199

REV
A

SHEET 1 OF 1

A	3539	RELEASE	MJUST	7/18/18
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY:	MJUST	DRAWING STATUS: Released		
DATE:	3/15/18	PRODUCTION APPROVED FOR RELEASED STATUS ONLY		